

交叉滚子系列



| 十字交叉滚子 轴承类型 | 轴承 型号 | 外形尺寸 (mm) | | | | | | 额定基本负荷 | | 重量 kg |
|----------------|-------------|-----------|---------|-------|-------|-------|-------|-------------|----------------|----------|
| | | 小 内径 | 大 内径 | 外径 | 轴承宽度 | 外圈宽度 | 内圈宽度 | C_r KN | C_{or} KN | |
| CSG(CSF) 型 | CSG(CSF)-14 | 11 | | 55 | 16.50 | 16.00 | 13.50 | 4.70 | 6.70 | 0.210 |
| | CSG(CSF)-17 | 10 | | 62 | 16.50 | 16.00 | 13.50 | 5.30 | 7.50 | 0.250 |
| | CSG(CSF)-20 | 14 | | 70 | 16.50 | 16.00 | 13.50 | 5.80 | 9.00 | 0.300 |
| | CSG(CSF)-25 | 20 | | 85 | 18.50 | 18.00 | 16.50 | 9.60 | 15.10 | 0.500 |
| | CSG(CSF)-32 | 26 | | 112 | 22.50 | 21.50 | 19.00 | 15.00 | 25.00 | 1.100 |
| CSD 型 | CSD-14 | 11.0 | 12.0 | 55 | 16.60 | 16.10 | 13.90 | 4.70 | 6.70 | 0.240 |
| | CSD-17 | 11.0 | 14.0 | 62 | 16.60 | 16.10 | 13.90 | 5.30 | 7.50 | 0.300 |
| | CSD-20 | 16.0 | 18.0 | 70 | 18.30 | 17.80 | 15.60 | 5.80 | 9.00 | 0.420 |
| | CSD-25 | 20.0 | 24.0 | 85 | 23.40 | 22.90 | 20.00 | 9.60 | 15.10 | 0.800 |
| | CSD-32 | 30.0 | 32.0 | 112 | 24.50 | 23.50 | 20.90 | 15.00 | 25.00 | 1.400 |
| SHG(SHF) 型 | SHG(SHF)-14 | 36.0 | 38.0 | 70 | 15.10 | 14.10 | 14.60 | 5.80 | 8.60 | 0.250 |
| | SHG(SHF)-17 | 44.1 | 47.0 | 80 | 17.00 | 16.00 | 16.40 | 10.40 | 16.30 | 0.350 |
| | SHG(SHF)-20 | 53.0 | 54.0 | 90 | 18.50 | 17.50 | 17.50 | 14.60 | 22.00 | 0.500 |
| | SHG(SHF)-25 | 65.0 | 67.0 | 110 | 20.70 | 18.70 | 19.70 | 21.80 | 35.80 | 0.800 |
| | SHG(SHF)-32 | 84.0 | 88.0 | 142 | 24.40 | 23.40 | 23.40 | 38.20 | 65.40 | 1.650 |
| CSD-2UF 型 | CSD-14-2UF | 11.0 | 30.0 | 70 | 16.50 | 16.00 | 14.70 | 5.80 | 8.60 | 0.400 |
| | CSD-17-2UF | 11.0 | 34.0 | 80 | 16.90 | 16.40 | 14.90 | 10.40 | 16.30 | 0.500 |
| | CSD-20-2UF | 20.0 | 40.0 | 90 | 20.30 | 18.00 | 17.80 | 14.60 | 22.00 | 0.700 |
| | CSD-25-2UF | 24.0 | 52.0 | 110 | 23.50 | 21.40 | 21.00 | 21.80 | 35.80 | 1.200 |
| | CSD-32-2UF | 32.0 | 70.0 | 142 | 27.40 | 24.60 | 24.50 | 38.20 | 65.40 | 2.300 |
| SHD 型 | SHD-14 | 39 | | 70 | 13.10 | 13.10 | 9.60 | 2.90 | 4.30 | ... |
| | SHD-17 | 45.8 | 47.8 | 80 | 13.50 | 13.50 | 8.90 | 5.20 | 8.10 | ... |
| | SHD-20 | 54.2 | 56.8 | 90 | 14.00 | 14.00 | 9.70 | 7.30 | 11.00 | ... |
| | SHD-25 | 67.0 | 69.5 | 110 | 16.70 | 16.70 | 10.90 | 15.60 | 31.10 | ... |
| | SHD-32 | 88 | | 142 | 20.00 | 20.00 | 12.50 | 19.10 | 32.70 | ... |
| 定制型 | HRBT355 | 35 | | 46 | 5.00 | 5.00 | 5.00 | 2.05 | 2.42 | 0.023 |
| | SHD-11-T | 29.5 | 31 | 52 | 9.45 | 9.45 | 7.05 | 3.30 | 4.80 | ... |
| | CSUD-14 | 11 | 18 | 41 55 | 12.20 | 10.70 | 10.10 | 4.22 | 5.22 | ... |
| | CSUD-20 | 16 | 28.5 | 56 70 | 12.10 | 10.60 | 10.10 | 5.13 | 7.73 | ... |

★本公司保留修改表中技术规则和其它数据的权利。